

# Brisa & Brisa Distressed — Ultrafabrics

Inspired by calming effects of nature, we introduce a curated palette that brings the beauty of outdoors in.



Brisa  
**Shiitake (USH)**

**Earth** – Rich, organic shades celebrate our love for natural materials and ground us.



Brisa Distressed  
**Buckskin (UBS)**



Brisa Distressed  
**Bridle (UBR)**



Brisa  
**Beet Root (UBE)**



Brisa  
**Coffee Bean (UCB)**



Brisa  
**Black Onyx (UBO)**

**Water** – Timeless shades that represent the depths found in the open seas.



Brisa  
**Cream (UCR)**




Brisa  
**Sterling Blue (USB)**



Brisa  
**Arctic (UAR)**



Brisa  
**Night Navy (UNN)**




Brisa Distressed  
**Iron (UIR)**

**Wind** – From a warm, calming breeze, to a crisp gentle air, wind symbolizes renewal and healing.



Brisa Distressed  
**Ranchwood (URW)**



Brisa Distressed  
**Saddle (USA)**




Brisa  
**Shiitake (USH)**



Brisa  
**Dill (UDI)**



Brisa  
**Celery (UCE)**



# Brisa & Brisa Distressed from Ultrafabrics

## Applications

Interior Upholstery

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
65% Polyester, 35% Rayon Backing

### Weight:

Approx. 8.9 oz. Per Square Yard  
Approx. 300 Grams Per Square Metre

### Thickness:

Approx. 0.95 Millimetres

### Width:

54 Inches / 137 Centimetres

### Repeat:

None

## Performance

### Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)\*  
BS EN ISO 12947-2 / 160,000 Rubs (Martindale)\*  
\*meets or exceeds

### Hydrolysis:

16 Weeks  
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D751

Tensile Strength: BS EN ISO 1421

Air Permeability: ASTM D737

Sound Absorption: ASTM C423

## Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4  
ISO 105 B02, Grade 6

Crocking: AATCC 8, Grade 4-5 Wet & Dry

## Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

\* Only in North America

## You Have To Feel It To Believe It

- 01 Exceptional wear resistance
- 02 Plush and luxurious feel enhances comfort
- 03 Climate control technology regulates temperature changes
- 04 Easy to care for and bleach cleanable
- 05 Animal free
- 06 Free of harmful Per- and polyfluoroalkyl substances (PAS)
- 07 No PVC, plasticizers, or other toxic chemicals
- 08 Low VOC's support healthier indoor air quality
- 09 Indoor Advantage Gold Certified



Golden Technologies  
401 Bridge St,  
Old Forge, PA 18518  
T 800-624-6374  
www.goldentech.com



ultrafabricsinc.com  
Ultrafabrics® and logo, and Brisa® are registered trademarks of Ultrafabrics Inc. Made in Japan.

